


LAMP PHOTOMETRIC REPORT

MODEL: 92FLCOM1040/BL		
POWER: W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 723.89 lm



$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%
10	1016	1007	998.1	995.6	996.2	1001	1001	1013	0- 10	107.7	107.7	14.9
20	615.1	618.4	604.7	607.9	608.1	614.2	611.9	613.4	10- 20	220.6	328.3	45.4
30	349.8	346.8	339.9	337.6	334.4	331.1	337.4	343.8	20- 30	210.7	539.0	74.5
40	115.0	118.4	112.4	104.7	94.00	87.77	90.31	102.9	30- 40	149.4	688.3	95.1
50	9.590	9.629	9.078	9.097	8.929	8.740	8.355	8.617	40- 50	24.69	713.0	98.5
60	4.734	4.956	4.779	4.866	4.714	4.717	4.512	4.603	50- 60	5.872	718.9	99.3
70	2.658	2.847	2.811	2.878	2.553	2.604	2.646	2.655	60- 70	3.594	722.5	99.8
80	0.0603	0.0555	0.0380	0.0658	0.0513	0.0368	0.0409	0.0314	70- 80	1.362	723.9	100
90	0.0081	0.0054	0.0054	0.0027	0.0163	0.0163	0.0163	0.0164	80- 90	0.0186	723.9	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3°C  
Operators:  
Test Date:24 August 2022

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 2.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity:65.0%  
Test Distance:6.265m [K=1.0000]  
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```