



## LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 99XLED638W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 225	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	99XLED638W	I <sub>max</sub> (cd)	434.5	S/MH (C0/180)	1.27
NOMINAL POWER (W)	18	LOR (%)	79.2	S/MH (C90/270)	1.28
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	1267.0	η UP, DN (C0-180)	0.0, 39.2
NOMINAL FLUX (lm)	1600	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 40.0
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	230	η down (%)	79.2	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature: 25.3°C  
Operators:  
Test Date: 25 October 2022

γ Range: 0 - 90DEG  
γ Interval: 2.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity: 65.0%  
Test Distance: 6.265m [K=1.0000]  
Remarks:

### ZONAL FLUX DIAGRAM

#### ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	427.1	426.7	426.6	426.9	427.4	428.0	428.1	427.8	0- 10	41.13	41.13	3.25,2.57
20	405.4	404.5	404.4	404.9	405.9	407.0	407.5	406.9	10- 20	118.1	159.2	12.6,9.95
30	370.1	368.8	368.7	369.4	370.7	372.4	373.2	372.3	20- 30	179.7	338.9	26.8,21.2
40	322.4	320.6	320.6	321.3	322.8	325.0	326.2	325.1	30- 40	217.9	556.8	44,34.8
50	263.4	261.3	261.3	262.0	263.8	266.3	267.9	266.6	40- 50	227.4	784.2	61.9,49
60	195.3	193.1	193.4	193.8	195.3	198.3	200.6	199.1	50- 60	206.4	990.6	78.2,61.9
70	121.8	120.1	121.3	121.2	121.6	124.9	128.0	126.6	60- 70	158.2	1149	90.7,71.8
80	51.23	50.02	51.23	51.31	51.00	54.17	57.32	55.91	70- 80	92.09	1241	97.9,77.6
90	0.7076	0.7160	0.7348	0.7226	0.6151	0.6208	0.6586	0.6355	80- 90	26.00	1267	100,79.2
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 671.25 lm

%lum = 53.0%  
%lamp = 42.0%

Conical surface Flux(130deg): 1077.2 lm


%lum = 85.0%  
%lamp = 67.3%

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature:25.3°C  
Operators:  
Test Date:25 October 2022

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 2.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity:65.0%  
Test Distance:6.265m [K=1.0000]  
Remarks:

### LUMINANCE LIMITATION CURVES

NAME: 99XLED638W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 225	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	9676	9371
80	11601	11602
75	12989	12953
70	14000	13944
65	14786	14683
60	15359	15213
55	15792	15655
50	16115	15989
45	16362	16254


C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature: 25.3°C  
Operators:  
Test Date: 25 October 2022

γ Range: 0 - 90DEG  
γ Interval: 2.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity: 65.0%  
Test Distance: 6.265m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 99XLED638W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 225	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature:25.3°C  
Operators:  
Test Date:25 October 2022

γ Range: 0 - 90DEG  
γ Interval: 2.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity:65.0%  
Test Distance:6.265m [K=1.0000]  
Remarks:

## WEC AND CCEC

NAME: 99XLED638W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 225	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.248	.141	.045	.243	.138	.044	.232	.133	.043	.223	.128	.041	.214	.124	.040	
2.0	.233	.128	.039	.228	.126	.039	.219	.122	.038	.210	.118	.037	.203	.115	.036	
3.0	.216	.115	.034	.211	.113	.034	.203	.110	.033	.195	.107	.033	.188	.104	.032	
4.0	.199	.103	.030	.195	.102	.030	.188	.099	.030	.181	.097	.029	.174	.095	.029	
5.0	.184	.094	.027	.180	.092	.027	.174	.090	.027	.168	.088	.026	.162	.087	.026	
6.0	.170	.085	.024	.167	.084	.024	.161	.083	.024	.156	.081	.024	.151	.079	.024	
7.0	.158	.078	.022	.156	.077	.022	.150	.076	.022	.146	.075	.022	.141	.073	.022	
8.0	.148	.072	.020	.145	.072	.020	.141	.070	.020	.136	.069	.020	.132	.068	.020	
9.0	.138	.067	.019	.136	.066	.019	.132	.065	.019	.128	.064	.018	.125	.063	.018	
10.0	.130	.062	.017	.128	.062	.017	.124	.061	.017	.121	.060	.017	.118	.059	.017	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.151	.151	.151	.129	.129	.129	.088	.088	.088	.051	.051	.051	.016	.016	.016	
1.0	.143	.124	.106	.122	.106	.091	.084	.073	.063	.048	.042	.037	.015	.014	.012	
2.0	.137	.104	.077	.117	.090	.067	.080	.062	.047	.046	.036	.027	.015	.012	.009	
3.0	.131	.091	.059	.112	.078	.051	.077	.054	.036	.044	.032	.021	.014	.010	.007	
4.0	.125	.080	.046	.107	.069	.040	.073	.048	.028	.043	.028	.017	.014	.009	.005	
5.0	.119	.072	.037	.102	.062	.032	.070	.043	.023	.041	.025	.014	.013	.008	.004	
6.0	.113	.065	.031	.097	.056	.027	.067	.039	.019	.039	.023	.011	.013	.008	.004	
7.0	.108	.060	.026	.092	.052	.023	.064	.036	.016	.037	.021	.010	.012	.007	.003	
8.0	.102	.055	.023	.088	.048	.020	.061	.034	.014	.035	.020	.008	.011	.006	.003	
9.0	.098	.051	.020	.084	.044	.017	.058	.031	.012	.034	.018	.007	.011	.006	.002	
10.0	.093	.048	.018	.080	.042	.015	.056	.029	.011	.032	.017	.007	.011	.006	.002	

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature:25.3°C  
Operators:  
Test Date:25 October 2022

γ Range: 0 - 90DEG  
γ Interval: 2.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity:65.0%  
Test Distance:6.265m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

NAME: 99XLED638W					TYPE:					WEIGHT: 1				
SPEC.:					DIM.: F 225					SERIAL No.: 0				
MFR.: Elmark Industries JSC					SUR.: round					Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H	20.8	22.3	21.1	22.5	22.7	20.8	22.3	21.0	22.5	22.7				
3H	22.3	23.7	22.6	24.0	24.2	22.3	23.7	22.6	23.9	24.2				
4H	22.9	24.3	23.2	24.5	24.8	22.9	24.2	23.2	24.5	24.8				
6H	23.3	24.6	23.7	24.9	25.2	23.3	24.6	23.7	24.9	25.2				
8H	23.5	24.7	23.8	25.0	25.3	23.5	24.7	23.8	25.0	25.3				
12H	23.5	24.7	23.9	25.0	25.3	23.5	24.7	23.9	25.0	25.3				
4H 2H	21.4	22.8	21.7	23.0	23.3	21.4	22.7	21.7	23.0	23.2				
3H	23.1	24.3	23.5	24.6	24.9	23.1	24.3	23.4	24.6	24.9				
4H	23.8	24.9	24.2	25.2	25.6	23.8	24.9	24.2	25.2	25.5				
6H	24.4	25.3	24.8	25.7	26.0	24.4	25.3	24.8	25.7	26.0				
8H	24.5	25.4	25.0	25.8	26.2	24.5	25.4	25.0	25.8	26.2				
12H	24.7	25.5	25.1	25.9	26.3	24.6	25.5	25.1	25.9	26.3				
8H 4H	24.1	25.0	24.5	25.3	25.7	24.1	25.0	24.5	25.3	25.7				
6H	24.8	25.5	25.2	25.9	26.3	24.8	25.5	25.2	25.9	26.3				
8H	25.0	25.7	25.5	26.1	26.6	25.0	25.7	25.5	26.1	26.6				
12H	25.2	25.8	25.7	26.2	26.7	25.2	25.8	25.7	26.2	26.7				
12H 4H	24.1	24.9	24.5	25.3	25.7	24.1	24.9	24.5	25.3	25.7				
6H	24.8	25.5	25.3	25.9	26.4	24.8	25.5	25.3	25.9	26.4				
8H	25.1	25.7	25.6	26.1	26.6	25.1	25.7	25.6	26.1	26.6				
Variations with the observer position at spacings(CIE Pub.117):														
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2								
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3								
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3								

CIE Pub.117, 1600 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.6)  
Area: 0.025434 m2

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature:25.3°C  
Operators:  
Test Date:25 October 2022

γ Range: 0 - 90DEG  
γ Interval: 2.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity:65.0%  
Test Distance:6.265m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

NAME: 99XLED638W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 225	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	45	36	30	45	36	30	44	35	30	25
0.80	53	44	38	52	44	38	51	43	38	32
1.00	60	51	45	59	51	45	57	52	45	39
1.25	66	57	51	64	57	51	62	55	50	45
1.50	69	62	56	68	61	56	66	59	55	49
2.00	75	68	63	73	67	62	71	65	61	55
2.50	78	72	67	76	71	66	73	69	65	58
3.00	81	75	71	79	74	70	76	72	68	62
4.00	84	79	76	82	78	75	79	75	72	65
5.00	86	82	79	84	81	78	80	78	75	68
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature: 25.3°C  
Operators:  
Test Date: 25 October 2022

γ Range: 0 - 90DEG  
γ Interval: 2.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity: 65.0%  
Test Distance: 6.265m [K=1.0000]  
Remarks:

**ISOCANDELA DIAGRAM**

NAME: 99XLED638W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 225	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature: 25.3°C  
Operators:  
Test Date: 25 October 2022

γ Range: 0 - 90DEG  
γ Interval: 2.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity: 65.0%  
Test Distance: 6.265m [K=1.0000]  
Remarks:



**AAI Figure**

NAME: 99XLED638W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 225	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:




**Note:** The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: MEDIUM  
 Temperature: 25.3°C  
 Operators:  
 Test Date: 25 October 2022

γ Range: 0 - 90DEG  
 γ Interval: 2.5DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
 Humidity: 65.0%  
 Test Distance: 6.265m [K=1.0000]  
 Remarks:

**ISOLUX DIAGRAM**

NAME: 99XLED638W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 225	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature: 25.3°C  
Operators:  
Test Date: 25 October 2022

γ Range: 0 - 90DEG  
γ Interval: 2.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity: 65.0%  
Test Distance: 6.265m [K=1.0000]  
Remarks:

### LED Avg.L Report

NAME: 99XLED638W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 225	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	14786
L_0~180 (75) av	12946
L_0~180 (85) av	9703
L_90~270 (65) av	15002
L_90~270 (75) av	13438
L_90~270 (85) av	10550
L_45 (65) av	14886
L_45 (75) av	13207
L_45 (85) av	10188

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature:25.3°C  
Operators:  
Test Date:25 October 2022

γ Range: 0 - 90DEG  
γ Interval: 2.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity:65.0%  
Test Distance:6.265m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: MEDIUM  
 Temperature: 25.3°C  
 Operators:  
 Test Date: 25 October 2022

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 2.5DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
 Humidity: 65.0%  
 Test Distance: 6.265m [K=1.0000]  
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```